

SAMPLE QUESTION PAPER (THEORY)
CLASS: XII SESSION: 2024-25
COMPUTER SCIENCE (083)

Time allowed: 3 Hours

Maximum Marks: 70

General Instructions:

- This question paper contains 37 questions.
- All questions are compulsory. However, internal choices have been provided in some questions. Attempt only one of the choices in such questions
- The paper is divided into 5 Sections- A, B, C, D and E.
- Section A consists of 21 questions (1 to 21). Each question carries 1 Mark.
- Section B consists of 7 questions (22 to 28). Each question carries 2 Marks.
- Section C consists of 3 questions (29 to 31). Each question carries 3 Marks.
- Section D consists of 4 questions (32 to 35). Each question carries 4 Marks.
- Section E consists of 2 questions (36 to 37). Each question carries 5 Marks.
- All programming questions are to be answered using Python Language only.
- In case of MCQ, text of the correct answer should also be written.

Q No.	Section-A (21 x 1 = 21 Marks)	Marks
1.	State True or False: The Python interpreter handles logical errors during code execution.	(1)
2.	Identify the output of the following code snippet: <pre>text = "PYTHONPROGRAM" text=text.replace('PY', '#') print(text)</pre> <p>(A) #THONPROGRAM (B) ##THON#ROGRAM (C) #THON#ROGRAM (D) #YTHON#ROGRAM</p>	(1)
3.	Which of the following expressions evaluates to False? (A) not(True) and False (B) True or False (C) not(False and True) (D) True and not(False)	(1)
4.	What is the output of the expression? <pre>country='International' print(country.split("n"))</pre> <p>(A) ('I', 'ter', 'atio', 'al') (B) ['I', 'ter', 'atio', 'al'] (C) ['I', 'n', 'ter', 'n', 'atio', 'n', 'al'] (D) Error</p>	(1)

5.	<p>What will be the output of the following code snippet?</p> <pre>message= "World Peace" print(message[-2::-2])</pre>	(1)
6.	<p>What will be the output of the following code?</p> <pre>tuple1 = (1, 2, 3) tuple2 = tuple1 tuple1 += (4,) print(tuple1 == tuple2)</pre> <p>(A) True (B) False (C) tuple1 (D) Error</p>	(1)
7.	<p>If my_dict is a dictionary as defined below, then which of the following statements will raise an exception?</p> <pre>my_dict = {'apple': 10, 'banana': 20, 'orange': 30}</pre> <p>(A) my_dict.get('orange') (B) print(my_dict['apple', 'banana']) (C) my_dict['apple']=20 (D) print(str(my_dict))</p>	(1)
8.	<p>What does the list.remove(x) method do in Python?</p> <p>(A) Removes the element at index x from the list (B) Removes the first occurrence of value x from the list (C) Removes all occurrences of value x from the list (D) Removes the last occurrence of value x from the list</p>	(1)
9.	<p>If a table which has one Primary key and two alternate keys. How many Candidate keys will this table have?</p> <p>(A) 1 (B) 2 (C) 3 (D) 4</p>	(1)
10.	<p>Write the missing statement to complete the following code:</p> <pre>file = open("example.txt", "r") data = file.read(100) _____ #Move the file pointer to the beginning of the file next_data = file.read(50) file.close()</pre>	(1)
11.	<p>State whether the following statement is True or False: The finally block in Python is executed only if no exception occurs in the try block.</p>	(1)

12.	<p>What will be the output of the following code?</p> <pre> c = 10 def add(): global c c = c + 2 print(c,end='#') add() c=15 print(c,end='%') </pre> <p>(A) 12%15# (B) 15#12% (C) 12#15% (D) 12%15#</p>	(1)
13.	Which SQL command can change the degree of an existing relation?	(1)
14.	<p>What will be the output of the query?</p> <pre> SELECT * FROM products WHERE product_name LIKE 'App%'; </pre> <p>(A) Details of all products whose names start with 'App' (B) Details of all products whose names end with 'App' (C) Names of all products whose names start with 'App' (D) Names of all products whose names end with 'App'</p>	(1)
15.	<p>In which datatype the value stored is padded with spaces to fit the specified length.</p> <p>(A) DATE (B) VARCHAR (C) FLOAT (D) CHAR</p>	(1)
16.	<p>Which aggregate function can be used to find the cardinality of a table?</p> <p>(A) sum() (B) count() (C) avg() (D) max()</p>	(1)
17.	<p>Which protocol is used to transfer files over the Internet?</p> <p>(A) HTTP (B) FTP (C) PPP (D) HTTPS</p>	(1)

18.	Which network device is used to connect two networks that use different protocols? (A) Modem (B) Gateway (C) Switch (D) Repeater	(1)
19.	Which switching technique breaks data into smaller packets for transmission, allowing multiple packets to share the same network resources.	(1)
	Q20 and Q21 are Assertion(A) and Reason(R) based questions. Mark the correct choice as: (A) Both A and R are true and R is the correct explanation for A (B) Both A and R are true and R is not the correct explanation for A (C) A is True but R is False (D) A is False but R is True	
20.	Assertion (A): Positional arguments in Python functions must be passed in the exact order in which they are defined in the function signature. Reasoning (R): This is because Python functions automatically assign default values to positional arguments.	(1)
21.	Assertion (A): A SELECT command in SQL can have both WHERE and HAVING clauses. Reasoning (R): WHERE and HAVING clauses are used to check conditions, therefore, these can be used interchangeably.	(1)
Q No	Section-B (7 x 2=14 Marks)	Marks
22.	How is a mutable object different from an immutable object in Python? Identify one mutable object and one immutable object from the following: (1,2), [1,2], {1:1,2:2}, '123'	(2)
23.	Give two examples of each of the following: (I) Arithmetic operators (II) Relational operators	(2)
24.	If L1=[1,2,3,2,1,2,4,2, . . .], and L2=[10,20,30, . . .], then (Answer using builtin functions only) (I) A) Write a statement to count the occurrences of 4 in L1. OR B) Write a statement to sort the elements of list L1 in ascending order.	(2)

	<p>(II)</p> <p>A) Write a statement to insert all the elements of L2 at the end of L1.</p> <p style="text-align: center;">OR</p> <p>B) Write a statement to reverse the elements of list L2.</p>					
25.	<p>Identify the correct output(s) of the following code. Also write the minimum and the maximum possible values of the variable b.</p> <pre>import random a="Wisdom" b=random.randint(1,6) for i in range(0,b,2): print(a[i],end='#')</pre> <table border="1" data-bbox="300 723 1345 857"> <tr> <td data-bbox="300 723 810 790">(A) W#</td> <td data-bbox="810 723 1345 790">(B) W##</td> </tr> <tr> <td data-bbox="300 790 810 857">(C) W#s#</td> <td data-bbox="810 790 1345 857">(D) W###s#</td> </tr> </table>	(A) W#	(B) W##	(C) W#s#	(D) W###s#	(2)
(A) W#	(B) W##					
(C) W#s#	(D) W###s#					
26.	<p>The code provided below is intended to swap the first and last elements of a given tuple. However, there are syntax and logical errors in the code. Rewrite it after removing all errors. Underline all the corrections made.</p> <pre>def swap_first_last(tup) if len(tup) < 2: return tup new_tup = (tup[-1],) + tup[1:-1] + (tup[0]) return new_tup result = swap_first_last((1, 2, 3, 4)) print("Swapped tuple: " result)</pre>	(2)				
27.	<p>(I)</p> <p>A) What constraint should be applied on a table column so that duplicate values are not allowed in that column, but NULL is allowed.</p> <p style="text-align: center;">OR</p> <p>B) What constraint should be applied on a table column so that NULL is not allowed in that column, but duplicate values are allowed.</p>	(2)				

	<p>(II)</p> <p>A) Write an SQL command to remove the Primary Key constraint from a table, named MOBILE. M_ID is the primary key of the table.</p> <p style="text-align: center;">OR</p> <p>B) Write an SQL command to make the column M_ID the Primary Key of an already existing table, named MOBILE.</p>	
28.	<p>A) List one advantage and one disadvantage of star topology.</p> <p style="text-align: center;">OR</p> <p>B) Expand the term SMTP. What is the use of SMTP?</p>	(2)

Q No.	Section-C (3 x 3 = 9 Marks)	Marks
29.	<p>A) Write a Python function that displays all the words containing @cmail from a text file "Emails.txt".</p> <p style="text-align: center;">OR</p> <p>B) Write a Python function that finds and displays all the words longer than 5 characters from a text file "Words.txt".</p>	(3)
30.	<p>A) You have a stack named BooksStack that contains records of books. Each book record is represented as a list containing book_title, author_name, and publication_year. Write the following user-defined functions in Python to perform the specified operations on the stack BooksStack:</p> <p>(I) push_book(BooksStack, new_book): This function takes the stack BooksStack and a new book record new_book as arguments and pushes the new book record onto the stack.</p> <p>(II) pop_book(BooksStack): This function pops the topmost book record from the stack and returns it. If the stack is already empty, the function should display "Underflow".</p> <p>(III) peep(BookStack): This function displays the topmost element of the stack without deleting it. If the stack is empty, the function should display 'None'.</p> <p style="text-align: center;">OR</p> <p>(B) Write the definition of a user-defined function `push_even(N)` which accepts a list of integers in a parameter `N` and pushes all those integers which are even from the list `N` into a Stack named `EvenNumbers`. Write function pop_even() to pop the topmost number from the stack and returns it. If the stack is already empty, the function should display "Empty". Write function Disp_even() to display all element of the stack without deleting them. If the stack is empty, the function should display 'None'.</p>	(3)

For example:
 If the integers input into the list `VALUES` are:
 [10, 5, 8, 3, 12]
 Then the stack `EvenNumbers` should store:
 [10, 8, 12]

31. Predict the output of the following code:

```

d = {"apple": 15, "banana": 7, "cherry": 9}
str1 = ""
for key in d:
    str1 = str1 + str(d[key]) + "@" + "\n"
str2 = str1[:-1]
print(str2)

```

OR

Predict the output of the following code:

```

line=[4,9,12,6,20]
for I in line:
    for j in range(1,I%5):
        print(j, '#', end="")
print()

```

(3)

Q No.	Section-D (4 x 4 = 16 Marks)	Marks
-------	-------------------------------	-------

32. Consider the table ORDERS as given below

O_Id	C_Name	Product	Quantity	Price
1001	Jitendra	Laptop	1	12000
1002	Mustafa	Smartphone	2	10000
1003	Dhwani	Headphone	1	1500

Note: The table contains many more records than shown here.

A) Write the following queries:

- (I) To display the total Quantity for each Product, excluding Products with total Quantity less than 5.
- (II) To display the orders table sorted by total price in descending order.
- (III) To display the distinct customer names from the Orders table.

(4)

	<p>(IV) Display the sum of Price of all the orders for which the quantity is null.</p> <p style="text-align: center;">OR</p> <p>B) Write the output</p> <p>(I) <code>Select c_name, sum(quantity) as total_quantity from orders group by c_name;</code></p> <p>(II) <code>Select * from orders where product like '%phone%';</code></p> <p>(III) <code>Select o_id, c_name, product, quantity, price from orders where price between 1500 and 12000;</code></p> <p>(IV) <code>Select max(price) from orders;</code></p>																																											
33.	<p>A csv file "Happiness.csv" contains the data of a survey. Each record of the file contains the following data:</p> <ul style="list-style-type: none"> ● Name of a country ● Population of the country ● Sample Size (<i>Number of persons who participated in the survey in that country</i>) ● Happy (<i>Number of persons who accepted that they were Happy</i>) <p>For example, a sample record of the file may be: ['Signiland', 5673000, 5000, 3426]</p> <p>Write the following Python functions to perform the specified operations on this file:</p> <p>(I) Read all the data from the file in the form of a list and display all those records for which the population is more than 5000000.</p> <p>(II) Count the number of records in the file.</p>	(4)																																										
34.	<p>Saman has been entrusted with the management of Law University Database. He needs to access some information from FACULTY and COURSES tables for a survey analysis. Help him extract the following information by writing the desired SQL queries as mentioned below.</p> <p style="text-align: center;">Table: FACULTY</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>F_ID</th> <th>FName</th> <th>LName</th> <th>Hire_Date</th> <th>Salary</th> </tr> </thead> <tbody> <tr> <td>102</td> <td>Amit</td> <td>Mishra</td> <td>12-10-1998</td> <td>12000</td> </tr> <tr> <td>103</td> <td>Nitin</td> <td>Vyas</td> <td>24-12-1994</td> <td>8000</td> </tr> <tr> <td>104</td> <td>Rakshit</td> <td>Soni</td> <td>18-5-2001</td> <td>14000</td> </tr> <tr> <td>105</td> <td>Rashmi</td> <td>Malhotra</td> <td>11-9-2004</td> <td>11000</td> </tr> <tr> <td>106</td> <td>Sulekha</td> <td>Srivastava</td> <td>5-6-2006</td> <td>10000</td> </tr> </tbody> </table> <p style="text-align: center;">Table: COURSES</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>C_ID</th> <th>F_ID</th> <th>CName</th> <th>Fees</th> </tr> </thead> <tbody> <tr> <td>C21</td> <td>102</td> <td>Grid Computing</td> <td>40000</td> </tr> <tr> <td>C22</td> <td>106</td> <td>System Design</td> <td>16000</td> </tr> </tbody> </table>	F_ID	FName	LName	Hire_Date	Salary	102	Amit	Mishra	12-10-1998	12000	103	Nitin	Vyas	24-12-1994	8000	104	Rakshit	Soni	18-5-2001	14000	105	Rashmi	Malhotra	11-9-2004	11000	106	Sulekha	Srivastava	5-6-2006	10000	C_ID	F_ID	CName	Fees	C21	102	Grid Computing	40000	C22	106	System Design	16000	(4)
F_ID	FName	LName	Hire_Date	Salary																																								
102	Amit	Mishra	12-10-1998	12000																																								
103	Nitin	Vyas	24-12-1994	8000																																								
104	Rakshit	Soni	18-5-2001	14000																																								
105	Rashmi	Malhotra	11-9-2004	11000																																								
106	Sulekha	Srivastava	5-6-2006	10000																																								
C_ID	F_ID	CName	Fees																																									
C21	102	Grid Computing	40000																																									
C22	106	System Design	16000																																									

	<table border="1"> <tr> <td>C23</td> <td>104</td> <td>Computer Security</td> <td>8000</td> </tr> <tr> <td>C24</td> <td>106</td> <td>Human Biology</td> <td>15000</td> </tr> <tr> <td>C25</td> <td>102</td> <td>Computer Network</td> <td>20000</td> </tr> <tr> <td>C26</td> <td>105</td> <td>Visual Basic</td> <td>6000</td> </tr> </table> <p>(I) To display complete details (from both the tables) of those Faculties whose salary is less than 12000.</p> <p>(II) To display the details of courses whose fees is in the range of 20000 to 50000 (both values included).</p> <p>(III) To increase the fees of all courses by 500 which have "Computer" in their Course names.</p> <p>(IV) (A) To display names (FName and LName) of faculty taking System Design.</p> <p style="text-align: center;">OR</p> <p>(B) To display the Cartesian Product of these two tables.</p>	C23	104	Computer Security	8000	C24	106	Human Biology	15000	C25	102	Computer Network	20000	C26	105	Visual Basic	6000	
C23	104	Computer Security	8000															
C24	106	Human Biology	15000															
C25	102	Computer Network	20000															
C26	105	Visual Basic	6000															


35.	<p>A table, named STATIONERY, in ITEMDB database, has the following structure:</p> <table border="1"> <thead> <tr> <th>Field</th> <th>Type</th> </tr> </thead> <tbody> <tr> <td>itemNo</td> <td>int(11)</td> </tr> <tr> <td>itemName</td> <td>varchar(15)</td> </tr> <tr> <td>price</td> <td>float</td> </tr> <tr> <td>qty</td> <td>int(11)</td> </tr> </tbody> </table> <p>Write the following Python function to perform the specified operation: AddAndDisplay(): To input details of an item and store it in the table STATIONERY. The function should then retrieve and display all records from the STATIONERY table where the Price is greater than 120.</p> <p>Assume the following for Python-Database connectivity: Host: localhost, User: root, Password: Pencil</p>	Field	Type	itemNo	int(11)	itemName	varchar(15)	price	float	qty	int(11)	(4)
Field	Type											
itemNo	int(11)											
itemName	varchar(15)											
price	float											
qty	int(11)											

Q.No.	SECTION E (2 X 5 = 10 Marks)	Marks
36.	<p>Surya is a manager working in a recruitment agency. He needs to manage the records of various candidates. For this, he wants the following information of each candidate to be stored:</p> <ul style="list-style-type: none"> - Candidate_ID – integer - Candidate_Name – string - Designation – string - Experience – float <p>You, as a programmer of the company, have been assigned to do this job for Surya.</p> <p>(I) Write a function to input the data of a candidate and append it in a binary file.</p>	(5)

(II) Write a function to update the data of candidates whose experience is more than 10 years and change their designation to "Senior Manager".
 (III) Write a function to read the data from the binary file and display the data of all those candidates who are not "Senior Manager".

37.

Event Horizon Enterprises is an event planning organization. It is planning to set up its India campus in Mumbai with its head office in Delhi. The Mumbai campus will have four blocks/buildings - ADMIN, FOOD, MEDIA, DECORATORS. You, as a network expert, need to suggest the best network-related solutions for them to resolve the issues/problems mentioned in points (I) to (V), keeping in mind the distances between various blocks/buildings and other given parameters.



Block to Block distances (in Mtrs.)

From	To	Distance
ADMIN	FOOD	42 m
ADMIN	MEDIA	96 m
ADMIN	DECORATORS	48 m
FOOD	MEDIA	58 m
FOOD	DECORATORS	46 m
MEDIA	DECORATORS	42 m

Distance of Delhi Head Office from Mumbai Campus = 1500 km
 Number of computers in each of the blocks/Center is as follows:

ADMIN	30
FOOD	18
MEDIA	25
DECORATORS	20
DELHI HEAD OFFICE	18

(5)

	<p>(I) Suggest the most appropriate location of the server inside the MUMBAI campus. Justify your choice.</p> <p>(II) Which hardware device will you suggest to connect all the computers within each building?</p> <p>(III) Draw the cable layout to efficiently connect various buildings within the MUMBAI campus. Which cable would you suggest for the most efficient data transfer over the network?</p> <p>(IV) Is there a requirement of a repeater in the given cable layout? Why/ Why not?</p> <p>(V) A) What would be your recommendation for enabling live visual communication between the Admin Office at the Mumbai campus and the DELHI Head Office from the following options:</p> <ul style="list-style-type: none">a) Video Conferencingb) Emailc) Telephonyd) Instant Messaging <p style="text-align: center;">OR</p> <p>B) What type of network (PAN, LAN, MAN, or WAN) will be set up among the computers connected in the MUMBAI campus?</p>	
--	---	--